



Stihl Gas Homeowner Trimmer - FS 38

[Read More](#)

SKU: FS-38

Categories: [STIHL](#)

Product Description

Features

TapAction™ AUTOCUT® Cutting Head -TapAction™ allows users to adjust the line length simply by tapping the cutting head against the ground.

Loop Handle (R) -Loop handle grass trimmers and brushcutters are ideal for trimming between bushes and shrubs and other areas where space is limited.

Air Filter Cover -Easily remove the cover for fast and easy filter cleaning or replacement.

Protected Spark Plug -The spark plug is protected yet easy to change.

Protected Choke Lever/Knob -**High-Tech Polymer Housing** -

Heavy-Duty Steel-On-Steel Clutch -Centrifugal clutch is designed to reduce slippage.

Purge Pump Primer -By pressing the bulb, this small fuel pump delivers fuel to the carburetor, reducing the number of starting pulls needed after an extended break between uses.

Easily check the fuel level before starting work. If fuel is needed, the upright position makes the tank easier to fill.

Lining provides smooth operation and low vibration.

Throttle Trigger Interlock -This safety feature must be depressed before the trigger can be activated.

Warnings and Safety

Note: STIHL recommends use of fuel with no more than 10% Ethanol content. Using fuel with greater than 10% Ethanol content may cause damage to your equipment and may void your STIHL warranty.

WARNING! Improper use of any trimmer/brushcutter can cause serious or fatal injury. Read, understand, and follow all safety instructions in your instruction manual. To reduce the risk of injury from blade contact, circular saw blades may be used on FS brushcutters that have a limitstop, a bicycle handle, and double shoulder harness and not on FS brushcutters with a "J" handle or loop handle. Other rigid blades may be used on FS brushcutters having a bicycle handle, a "J" handle, or a loop handle equipped with a barrier bar. To reduce the risk of eye injury always wear proper eye protection. Always use the appropriate deflector for the type of cutting attachment, as explained in your instruction manual.

